

**VORLANE**  
WWW.VORLANE.COM



## **LED FLOOD LIGHT SERIES**

VORLANE, YOUR DESIGN-DRIVEN PARTNER OF LED LIGHTS.  
TOP SUPPLY CHAIN & ISO-CERTIFIED FACTORIES.  
YOU HAVE VORLANE TEAM IN CHINA.



## Model: IP 65 LED Flood Light

### SPECIFICATIONS

Power: 50W/100W/200W/300W  
 Voltage: 220V/AC  
 Lumens: 110LM/W  
 CRI: >65Ra  
 Colour Temp: 3000-6000K  
 Protection level: IP65  
 Beam angle: 120°  
 Material: Die-cast aluminum+Tempered glass

Power	Dimension
50W	L210*H240*W60mm
100W	L235*H280*W65mm
200W	L280*H312*W70mm
300W	L310*H340*W70mm



## Model: LED Flood Light-LYS

### SPECIFICATIONS

Power: 50W/100W/150W/200W/250W/300W/400W/500W/600W  
 Voltage: 85~265V/AC  
 Lumens: 100-120LM/W  
 CRI: >70Ra  
 PF: >0.95  
 Colour Temp: 2700-7000K  
 Protection level: IP65  
 Beam angle: 90°/70°\*140°  
 Material: Die-cast aluminum+PC

Power	Dimension	Power	Dimension
50W	L340*H170*W100mm	300W	L355*H495*W105mm
100W	L355*H170*W100mm	400W	L685*H370*W105mm
150W	L355*H250*W105mm	500W	L685*H450*W105mm
200W	L355*H330*W105mm	600W	L685*H530*W105mm
250W	L355*H415*W105mm		



## Model: LED Flood Light-XGS

### SPECIFICATIONS

Power: 50W/100W/150W/200W/300W  
 Voltage: 85~265V/AC  
 Lumens: 90-100LM/W  
 CRI: >70Ra  
 PF: >0.90  
 Colour Temp: 2700-7000K  
 Protection level: IP65  
 Beam angle: 120°  
 Material: Die-cast aluminum+Tempered glass

Power	Dimension
50W	L185*H230*W45mm
100W	L245*H295*W55mm
150W	L275*H330*W60mm
200W	L330*H380*W65mm
300W	L395*H440*W65mm



## Model: LED Flood Light-XJS

### SPECIFICATIONS

Power: 50W/100W/150W/200W/300W/400W  
 Voltage: 85~265V/AC  
 Lumens: 90-110LM/W  
 CRI: >70Ra  
 PF: >0.9  
 Colour Temp: 2700-7000K  
 Protection level: IP44  
 Beam angle: 90°  
 Material: Die-cast aluminum+Tempered glass

Power	Dimension
50W	L175*H245*W45mm
100W	L235*H325*W50mm
150W	L285*H345*W55mm
200W	L285*H420*W55mm
300W	L350*H485*W55mm
300W	L400*H560*W55mm





## Model: LED Flood Light-YTS-Solar

### SPECIFICATIONS

Power: 25W/40W/60W/120W/200W  
 Rechargeable time: 4.5H  
 Discharge time: 12H  
 Colour Temp: 6000-6500K  
 Protection level: IP65  
 Beam angle: 120°  
 Operating mode: Light control + Remote control  
 Material: Die-cast aluminum+Tempered glass

Power	Solar panel	Battery
25W	L350*H230mm/6V 8W	5AH
40W	L350*H290mm/6V 12W	6AH
60W	L350*H350mm/6V 15W	10AH
120W	L350*H530mm/6V 25W	20AH
200W	L350*H670mm/6V 35W	25AH



## Model: LED Flood Light-XJS-Solar

### SPECIFICATIONS

Power: 100W/200W/300W/400W  
 Charge time: 4H  
 Working time: 12H  
 Colour Temp: 6000-6500K  
 Protection level: IP65  
 Beam angle: 90°  
 Operating mode: light control + radar sensor + remote control  
 Material: Die-cast aluminum+Tempered glass

Power	Lamp size	Solar panel size	Battery
100W	155*215*35mm	350*230*17mm/6V 8W	6AH
200W	214*290*47mm	350*230*17mm/6V 15W	12AH
300W	260*318*55mm	530*350*17mm/6V 25W	18AH
400W	267*372*55mm	350*610*17mm/6V 30W	24AH



## Model: LED Light-XYS-Solar

### SPECIFICATIONS

Power: 100W/200W/300W  
 Charge time: 4-5H  
 Working time: 12H  
 Colour Temp: 6000-6500K  
 Protection level: IP65  
 Beam angle: 90°  
 Operating mode: Light control + time control + remote control  
 Material: Die-cast aluminum+Tempered glass

Power	Lamp size	Solar panel size	Battery
100W	210*211*38mm	350*235x17mm/6V 15W	12AH
200W	233*238*43mm	350*450x17mm/6V 30W	24AH
300W	274*261*45mm	350*700*17mm/6V 40W	36AH



# VORLANE

WWW.VORLANE.COM

WELCOME  
TO CALL US

Mobile: 13925366726

Email : [sales@vorlane.com](mailto:sales@vorlane.com)

